

AQT-MSV-34 VALVES | SPECIFICATIONS

DESCRIPTION

Control Type	Manual
Electricity	None Required
Water Capacity Service	9 gpm @ 21.8 psi
Water Capacity Back Wash	4 gpm @ 21.8 psi

VALVE SPECIFICATIONS

Inlet/Outlet	3/4"
Mounting Base	2.5" - 8 NPSM
Drain Line	1/2"
Riser Pipe	1.05" OD
Brine Line	3/8"

ADDITIONAL INFORMATION

Temp Range	41 °F (5 °C) – 113 °F (45 °C)
Pressure Range	14 psi - 87 psi

MATERIALS OF CONSTRUCTION:

Body	Noryl
Handle	Plastic
Internal Disc	Ceramic

TANK SIZE RANGE (recommended)

Softener	6" - 10"
----------	----------

AQT-MSV-1 VALVES | SPECIFICATIONS

DESCRIPTION

Control Type	Manual
Electricity	None Required
Water Capacity Service	19 gpm @ 21.8 psi
Water Capacity Back Wash	6.7 gpm @ 21.8 psi

VALVE SPECIFICATIONS

Inlet/Outlet	1"
Mounting Base	2.5" - 8 NPSM
Drain Line	1/2"
Riser Pipe	1.05" OD
Brine Line	3/8"

ADDITIONAL INFORMATION

Temp Range	41 °F (5 °C) – 113 °F (45 °C)
Pressure Range	14 psi - 87 psi

MATERIALS OF CONSTRUCTION:

Body	Noryl
Handle	Metal
Internal Disc	Ceramic

TANK SIZE RANGE (recommended)

Softener	6"-16"
----------	--------

AQT-MSV-34 & AQT-MSV-1 Manual Softener Valves

Aquatrol AQT-MSV-34 & AQT-MSV-1 Manual Softener Valves

offer a simple to use manually controlled valve for easy operation. Used for water softening and other water treatment applications. The Aquatrol AQT-MSV-34 & AQT-MSV-1 Manual Softener Valves are available in 2.5" base and provide an easy to use lever for ease of operation.

