



New Ranges to 60,000 psi (4200 bar)



We designed the 680 series digital pressure gauges with two main objectives in mind. First, to provide an affordable digital gauge to replace mechanical gauges. If you're looking to move from dial gauges to a digital gauge, you'll find the 680 standard version gauge to be of high quality and suited for your need in terms of price and performance. With advanced microprocessor technology and state-of-the-art silicon pressure sensors, the 680 series digital pressure gauges provide an accurate, reliable, and economic solution for a wide range of pressure applications. They are loaded with functionality and remarkably easy to use. To reach the best performance, every silicon pressure sensor is specially aged, tested and screened before assembly.

The second objective was to provide a high-precision pressure gauge capable of wireless communication and data logging. Our 680W series provides just this along with several accuracy and pressure range options to meet your need. This wireless unit is compatible with the Additel/Land Wireless software, which is available for a free download from our website. Data can be recorded standalone with the 680W and then downloaded wirelessly to Additel/Land Wireless. For more advanced logging and data analysis, Additel/Log II Wireless is specially designed to communicate with the 680W. Each unit can store up to 140,000 readings which consist of date, time, pressure, and internal temperature. The 680 series digital pressure gauges are unmatched in performance and reliability. Best of all they are very affordable.

- Pressure ranges to 60,000 psi (4,200 bar)
- 0.05%, 0.1% or 0.25% full scale accuracy
- Fully temperature compensated accuracy from 14°F to 122°F (-10°C to 50°C)
- Up to 13 selectable pressure units, 6 customized definition engineering units
- Large, easy to read display with 5-digit resolution
- Backlit display
- Icon-based menu
- Display flash warning when pressure exceeds 120% of FS
- Stainless wetted surface construction
- IP67 (submersible in 1 meter of water)
- Drop-tested from 1 meter
- 2 AA alkaline batteries
- CE R&TTE, FCC ID, IC ID Certificates
- NIST traceable calibration with data(included)

	Digital Pressure Gauge	Wireless Digital Pressure Gauge with Data Logging
	Gauge Pressure, compound Pressure	
	0.05%, 0.1% or 0.25%FS	
	10 times/Sec ,3 times /Sec (default), 1 time /Sec ,1 time/15 Sec	
	14°F to 122°F (-10°C to 50°C)	
	14°F to 122°F (-10°C to 50°C), accuracy guaranteed	
	-4°F to 158°F (-20°C to 70°C)	
	1.2X	
	100mm x 40mm, total height:157mm	
	500g	




		Wireless Frequency: 2.4G ISM Bands, 20 meter range
	N/A	Number of wireless Channels : Chanel 1-15
		Software: Wireless network demo software included read upto 20 gauges.
	N/A	Storage Capacity: 140,000 readings (time, pressure, and temperature)
		Storage Interval: Adjustable from 1-9999 Sec
		Single-button-press data logging enabled
		Key Lockout: When the gauge is in auto-storing mode, the front panel buttons will be automatically locked.
	Averaging (3 to 10 samples) or low-pass frst-order filter.	
	Saves Max and Min data during pressure measurement.	
	Pa, kPa, MPa, bar, mba, psi, kgf/cm ² , mmH ₂ O, mmHg, inH ₂ O, inHg, ozf/in, %, °C, °F extend units: inH ₂ O(20°C), inH ₂ O(60°F), mmH ₂ O(20°C), mmH ₂ O(15°C), ftH ₂ O(60°F), or ftH ₂ O(4°C)	
	LCD Specifcation: FSTN-LCD,Visual scope 36x61mm	
	Full 5 digits,15.2mm High	
	7 segment analog bar graph scaled from 0-100% of FS	
	Backlight: White	
	Backlight Duration: Not auto off,15,30,45,60 seconds optional	
	Disabled,15, 30, 45, 60, 90, or 120 Minutes	
	Certificates:CE R&TTE, FCC ID, IC ID	
	Protection Level: IP67	
	Vibration: 5g(20-2000Hz)	
	Shock resistance: 100g/11ms	
	15,000 PSI: 1/4NPT male, 1/2NPT male, 1/4BSP male, 1/2BSP male, M20x1.5 male	
	>15,000 PSI: 1/4HP female or 1/4HP male	
	*1/4HP female: Autoclave F-250-C, 9/16" - 18 UNF-2B	
	*1/4HP male: Autoclave M-250-C, 9/16" - 18 UNF-2A	
	Other connections available per request.	
	Display will fash over 120%FS	
	Displays the battery life remaining. When the battery voltage is too low, the gauge will power-off automatically.	
	Gauge will record max pressure data when the gauge is over pressured by 120% of FS.	
	In leak test mode, the gauge will record beginning pressure, ending pressure, and » c , the" "	

Gauge Pressure					
P/N	Pressure Range		Accuracy(FS%)	Media ^[3]	Burst Pressure
	(psi) ^[1]	(bar)			
V15	-15	-1.0	0.05 (0.1, 0.25)	G	3x
GP15	15	1.0	0.05 (0.1, 0.25)	G,L	3x
GP30	30	2.0	0.05 (0.1, 0.25)	G,L	3x
GP100	100	7.0	0.05 (0.1, 0.25)	G,L	3x
GP150	150	10	0.05 (0.1, 0.25)	G,L	3x
GP300	300	20	0.05 (0.1, 0.25)	G,L	3x
GP500	500	35	0.05 (0.1, 0.25)	G,L	3x
GP1K	1,000	70	0.05 (0.1, 0.25)	G,L	3x
GP3K	3,000	200	0.05 (0.1, 0.25)	G,L	3x
GP5K	5,000	350	0.05 (0.1, 0.25)	G,L	3x
GP10K	10,000	700	0.05 (0.1, 0.25)	G,L	3x
GP15K	15,000	1,000	0.05 (0.1, 0.25)	G,L	2x
GP20K	20,000	1,400	0.05 (0.1, 0.25)	G,L	1.5x
GP25K	25,000	1,600	0.1 (0.25)	G,L	1.5x
GP30K	30,000	2,000	0.1 (0.25)	G,L	1.5x
GP36K	36,000	2,500	0.1 (0.25)	G,L	1.5x
GP40K	40,000	2,800	0.1 (0.25)	G,L	1.35x
GP50K	50,000	3,500	0.1 (0.25)	G,L	1.2x
GP60K	60,000	4,200	0.1 (0.25)	G,L	1.1x

[1] Sealed gauge pressure for above 1,000 psi.

[2] FS specification applies to the span of the range.

[3] G=Gas, L=Liquid



AA battery (2 pcs)
Rubber boot for Additel 680 gauge;
Additel/Land Wireless software for 680W (free download at www.additel.com)
Manual
NIST traceable calibration certificate

9503	Additel/Log II Wireless real time data logging and graphical software for 680W
9030	Spare wireless master device (USB dongle) for ADT680W gauge.

Note: For oil-free applications contact Additel.